

digiLITE



INDOOR & OUTDOOR
ULTRA LIGHTWEIGHT
SCREEN



LIGHT AS A FEATHER

Strong and yet light-weight the digiLITE screen system is ideal when weight is a pre requisite for an effective and yet robust screen system. Ideal for stadium gondolas and other suspended situations. Some models of the digiLITE series also benefit from transparency up to 65%.

THE LED
SCREEN
EXPERTS

		digiLITE 2840i	digiLITE 3910i	digiLITE 6910	digiLITE 8910
Pixel Configuration		SMD 3-in-1			
LED Type		SMD1415	SMD1921	-	-
Physical Pixel Pitch	mm	2.841	3.906	6.944	8.929
LED Face Colour		Black body			
Pixel Resolution (Width/Height)	pixels/tile	176/352	128/256	108/204	56/112
Viewing Angles	(H/V degrees)	TBC			
Tile/Panel Width	mm	500			
Tile/Panel Height	mm	1000			
Tile/panel Depth	mm	90			
Tile Area	m ²	0.5			
Standard Panel Weight	kg	11			
Ingress Protection		IP30/IP40	IP30/IP40	IP65/IP65	IP65/IP65
LED Fixings		Push fit			
Refresh Rate	Hz	≥3840			
Brightness Uncalibrated	nits	≥1000	≥1000	≥4500	≥4000
Brightness Calibrated	nits	≥800	≥800	≥4000	≥3500
Processing Depth		16.7m			
Input Voltage	VAC	110~220			
Input Power (Average)	watts/m ²	182	203	-	-
Input Power (Maximum)	watts/m ²	520	580	-	-
Transparency	%	0	0	35	30
Control System		NovaStar			
Certification		CE, RoHS, UL			

All specifications are correct at time of print, however they are liable to change and should be confirmed at point of order





digiLED

Contact T +44 20 7381 7840 info@digiLED.com www.digiLED.com

THE LED
SCREEN
EXPERTS